## 46081 PART A

Revision Date: 2013/04/11

## **Section 1: PRODUCT INFORMATION**

**Chemical family:** Mixture.

Product uses: Coating.

**Product name:** 46081 Part A.

Manufacturer: Flame Control Coatings Inc.

4120 Hyde Park Blvd.,

P.O.Box 786

Niagara Falls, New York, 14305.

Manufacturer emergency phone

number:

800-535-5053

Supplier: Same as manufacturer.

**TDG classification:** PAINT

PAINT UN1263 Class 3 PG III.

WHMIS classification:

B2, D2A, D2B.





**DSL status:** The substance(s) listed in section 2 appear on the Domestic Substances List.

**Supplier MSDS date:** 2013/04/11.

## **Section 2: HAZARDOUS INGREDIENTS**

C.A.S.	CONCENTRATION %	Ingrédient	V.L.E.	DL/50	CL/50
107-98-2	5-10	PROPYLENE GLYCOL METHYL ETHER	100 PPM	6600 MG/KG RAT ORAL 11,700 MG/KG MOUSE ORAL 5700 MG/KG RABBIT ORAL 13,000 MG/KG RABBIT DERMAL	10,000 PPM/5H RAT INHALATION
108-78-1	10–30	MELAMINE	NOT AVAILABLE	3161 MG/KG RAT ORAL 3296 MG/KG MOUSE ORAL >1000 MG/KG RABBIT DERMAL	3248 MG/M3 RAT INHALATION
13463-67-7	1-5	TITANIUM DIOXIDE	10 MG/M3	NOT AVAILABLE	NOT AVAILABLE
25068-38-6	10-30	BISPHENOL A/EPICHLOROHYDRIN EPOXY RESIN	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE
34590-94-8	5-10	DIPROPYLENE GLYCOL MONOMETHYL ETHER	100 PPM (SKIN)	5.400 MG/KG RAT ORAL 5.5 ML/KG RAT ORAL 10 ML/KG RABBIT DERMAL	>500 PPM RAT INHALATION
64742-95-6	1–5	LIGHT AROMATIC SOLVENT NAPHTHA (C8-C10)	NOT AVAILABLE	8400 MG/KG RAT ORAL	NOT AVAILABLE
87-74-2	1-5	1,2-BENZENEDICARBOXYLIC ACID, DIBUTYL ESTER	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE

#### Section 2A: ADDITIONAL INGREDIENT INFORMATION

Note: (supplier).

CAS# 87-74-2:TLV 5 mg/m3.

#### **Section 3: PHYSICAL DATA**

Physical state: Liquid.

Appearance & odor: Pigmented.

Aromatic solvent odour.

Odor threshold (ppm): Not available.

Vapour pressure (mmHg): (methoxypropanol).

8

Vapour density (air=1): 3.1

Volatiles (%)

By volume: 22%

**Evaporation rate** (butyl acetate = 1):

**Boiling point** (°C): (methoxypropanol).

246F (119C).

**Freezing point** (°C): Not available.

pH: Not applicable.

**Specific gravity @ 20 °C:** 1.25–1.35.

**Solubility in water (%):** Insoluble.

Coefficient of water\oil dist.: Not available.

VOC: 200 g/l.

### **Section 4: FIRE & EXPLOSION DATA**

Flammability: Flammable.

Conditions of flammability: Vapours are heavier than air and may travel along the ground and be ignited by

flames, sparks or other ignition sources at locations distant from the material

handling point.

Heat, sparks and open flames.

May cause flash fire.

**Extinguishing media:** Dry chemical.

Alcohol foam. Water fog. Carbon dioxide.

**Special procedures:** Self-contained breathing apparatus required.

Firefighters should wear the usual protective gear. Use water spray to cool fire exposed containers.

**Auto-ignition temperature** (°C): 530F (276C).

Flash point (°C), method: Tag Closed Cup.

(methoxypropanol). 91F (32.7C).

Lower flammability

limit (% vol):

Upper flammability 10.9%

limit (% vol):

**Explosion Data** 

Sensitivity to static discharge: Take precautionary measures against static discharge.

**Sensitivity to mechanical impact:** Not available.

**Hazardous combustion products:** Oxides of carbon (CO, CO2).

Acids Aldehydes.

Toxic and irritating vapours.

**Explosive power:** Contact with oxidizers may cause fire or explosion.

#### **Section 5: REACTIVITY DATA**

Chemical stability: Stable under normal conditions.

Conditions of instability: Explosive peroxides may form.

**Hazardous polymerization:** Will not occur.

**Incompatible substances:** Strong acids.

Oxidizing agents. Perchlorates. Nitrates. Peroxides. Hypochlorites. Phosphorous.

**Hazardous decomposition** 

products:

Oxides of carbon.

### **Section 6: TOXICOLOGICAL PROPERTIES**

Route of entry: Skin contact, eye contact, inhalation and ingestion.

Effects of acute exposure

Eye contact: May cause pain.

Severe irritant.

May cause swelling, redness and tearing.

Reversible corneal damage.

**Skin contact:** Pre–existing skin disorders may be aggravated by exposure.

May be absorbed through the skin and produce effects similar to those caused by

inhalation.

**Inhalation:** Harmful if inhaled.

May cause narcosis.

May cause loss of appetite.

May cause headache, dizziness and nausea.

May cause fatigue.

May cause tightness of the chest. May cause drying of throat.

**Ingestion:** May cause digestive tract irritation.

May cause nausea, vomiting and diarrhea.

May cause sore throat.

Aspiration of liquid into lungs may cause chemical pneumonitis which can be fatal.

May cause abdominal pain. Harmful or fatal if swallowed.

**Effects of chronic exposure:** May cause conjunctivitis.

May cause liver and kidney damage. May cause defatting and dermatitis.

Prolonged occupational overexposure to solvents may lead to permanent brain and

nervous system damage. May cause blood damage.

Allergies may be aggravated by this product. May cause drying and cracking of skin.

May cause loss of memory, loss of intellectual ability and loss of coordination.

**LD50 of product, species & route:** 5000 mg/kg rat oral.

4000 mg/kg rabbit dermal.

LC50 of product, species & route: Not available for mixture, see the ingredients section.

**Exposure limit of material:** Not available for mixture, see the ingredients section.

**Sensitization to product:** Sensitizer. **Carcinogenic effects:** Possible.

Reproductive effects: Not available.

**Teratogenicity:** May cause teratogenic effects.

Mutagenicity: None known.

Synergistic materials: None known.

# **Section 7: PREVENTATIVE MEASURES**

#### **Precautionary Measures**

Gloves/Type:



Nitrile rubber gloves.

Respiratory/Type: None normally required.

NIOSH approved respirator with organic vapor cartridge is required if ventilation is

inadequate or exposure limits are exceeded.

Eye/Type:





Safety glasses or goggles.

Footwear/Type: Safety shoes per local regulations.

**Clothing/Type:** Wear adequate protective clothes.

Long sleeve shirt, long trousers.

**Other/Type:** Eye wash facility should be in close proximity.

Emergency shower should be in close proximity.

**Ventilation requirements:** Exhaust ventilation.

To maintain exposure below TLV.

**Leak/Spill:** Eliminate all sources of ignition.

Prevent entry into drains, sewers, and other waterways.

Wear appropriate protective equipment.

Ground handling equipment. Cover with absorbent material. Place in metal container.

Waste disposal: Dispose in accordance with local, provincial/state, and federal regulations.

Incineration is the preferred method.

Handling procedures and Keep away from heat, sparks, and open flame.

equipment: Avoid breathing vapors/mists.

Use adequate ventilation.

Wash thoroughly after handling.

Empty containers containing residue may cause a hazard.

Wear personal material safety protection.

Use non-sparking tools.

Use proper grounding procedures.

Avoid contact with skin, eyes and clothing. Launder contaminated clothing prior to reuse.

Storage requirements: Store in a cool and well ventilated area.

Keep out of direct sunlight.

Keep away from heat, combustibles and reactive chemicals.

Keep containers tightly closed. Avoid extreme temperatures. Store in a sprinklered warehouse.

TDG classification:

PAINT UN1263 Class 3 PG III. \*\*\*

**Special shipping information:** See transportation information.

#### **Section 8: FIRST AID MEASURES**

**Skin contact:** Remove contaminated clothing.

Flush with large amounts of water, for at least 15 minutes.

Seek medical attention if irritation persists.

**Eye contact:** Flush with water for at least 15 minutes.

Obtain emergency medical attention.

Inhalation: Remove victim to fresh air. If not breathing, qualified personnel should administer

artificial respiration. Get medical attention.

**Ingestion:** Never give anything by mouth to an unconscious person.

Do not induce vomiting, seek immediate medical attention.

Drink 3 to 4 glasses of water or milk.

Additional information: The above information is believed to be correct but does not purport to be all

inclusive and shall be used only as a guide. This company shall not be held liable

for any inaccuracies.

# **Section 9: ADDITIONAL INFORMATION**

General note: This material safety data sheet was prepared from information obtained from various sources, including product suppliers and the Canadian Center for Occupational Health and Safety.

This MSDS was generated by Conform-Plus Application Service. Visit us at www.netmsds.com.